

Unmanaged PoE+ Switch

18 Ports Full Giga PoE Switch

DES-Q162GS2



**ELEVATE YOUR CONNECTIVITY WITH
OUR LATEST NETWORK SWITCHES**



DATASHEET

DES-Q162GS2

16*1000M POE+2*GE RJ45+2*SFP PoE Switch

- ☆ 16*10/100/1000M + 2*10/100/1000M RJ45 +2*100/1000M SFP Port PoE Switch,1-16 ports support IEEE 802.3af/at;
- ☆ Comply with IEEE 802.3, IEEE 802.3u,IEEE802.3ab,IEEE802.3z standards;
- ☆ PoE port support AF/AT intelligent recognition. Standard power is 15.4W/port, Maximum power: 30W/port;
- ☆ Support AI Watchdog, Port self-healing, VLAN, extend 300meter distance, Auto Speed Change, Priority port & reduce the after-resale;
- ☆ Supports POE devices such as wireless access points (APs) and network surveillance cameras through Category 5/6 Ethernet cables;
- ☆ The Power supply is 300W;
- ☆ 3 year warranty , (T&C)



Introduction;

The DES-Q162GS2 is an unmanaged PoE switch, it has 16*10/100/1000M PoE ports and 2*1000M uplink RJ45 and 2*100/1000M SFP ports, Port 1-16 can support IEEE 802.3af/at standard PoE power supply, single port PoE power up to 30W, and the maximum POE output power is 300W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP phone, video access control intercom, etc. through network cable to meet the network environment that needs high-density PoE power supply. It is suitable for hotels, campuses, factory quarters and small and medium-sized enterprises to form an economy. Efficient network.

DATASHEET

Technical Specifications;

Model	DES-Q162GS2
Fixed Port	16*10/100/1000Base-T/TX PoE ports (Data/Power) 2*10/100/1000Base-T/TX RJ45 ports (Data) 2*100/1000Base-X uplink SFP fiber slot (Data)
POE Port	Port 1-16 support PoE @ IEEE802.3af/at
Feature	With the Dial code switch, support port priority by default. E: AI Extend 300meters transmission and auto speed change of single port (limit 10Mbps), other ports maintain 100M/1000M within 100 meters; V: Turn on, 1-16 Port support each port Isolation & VLAN; D: Turn on, 1-16 Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem & reduce after-sale.
Fan	Non-Fan, silent working status can satisfy more users with different requirement
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000base-X; IEEE802.3u 100Base-FX; IEEE802.3x.
PoE Standard	IEEE802.3af/at
Ethernet Port	10/100/1000Base-T(X) automatic detection, full/half Duplex MDI/MDI-X adaptive
Switching Capacity	40Gbps (non-blocking)
Forwarding Rate	29.76Mpps
MAC	8K
Buffer Memory	4M
Twisted Pair Transmission	10BASE-T: Cat5 UTP (≤ 300 meter) 100BASE-TX: Cat5 or later UTP (≤ 100 meter) 1000BASE-T: Cat5 or later UTP (≤ 100 meter)
Power Supply Pin	Default 1/2(+), 3/6(-)
MAX / AVERAGE Power Per Port	30W/15.4W
Power Budget	200W
Power Consumption	Standby:<5W; Full load:<300W
LED Indicator	Power indicator: PWR (Green); Network indicator: 1-4(Link/Act)/ (Green),5-6(Link/Act)/ (Green)
Power Supply	Built in switching power supply, AC100~240V 50-60Hz
Operation TEMP / Humidity	-20~+55°C:5%~90% RH non condensing
Dimension	330*220*44mm

DATASHEET

Net /Gross Weight	<3kg
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV
Protection Level	IP30
Installation Method	desktop type, wall mounted,19-inch 1U cabinet installation
Certification	FCC; CE mark, commercial;CE/LVD EN60950; FCC Part 15 Class B;RoHS
Warranty	3 year warranty , (T&C)

Packaging List

CONTENT	QTY	UNIT
20 Ports Full Giga PoE Switch (DES-Q162GS2)	1	SET
Hanging Ear	1	Pair
User guide	1	SET
Warranty card	1	SET

