

IP PBX SYSTEM



DUC-200

"Driving Productivity Through
Unified Communication Solutions"

DUC-200

DUC-200 is an easy-to-config and delicate moderate-sized IPPBX system specially designed for SMEs. DUC-200 is well suited for enterprises with around 200 people, and it fulfills all the needs of an enterprise's office phone system. 200 can support GSM modules, WCDMA modules, analog trunks, SIP trunks, or other VoIP system integration. When used with the EX16S Expansion Box, 200 supports mixed networking of analog phones and IP phones. Equipped with the brand-new software 4.0 system, DUC-200 can provide users with more convenience in application and management. Plus, improve enterprise communication efficiency, and help enhance enterprise value

Feature Highlights

Endpoints Provisioning

Quick and straightforward deployment of endpoint devices using the Plug-and-Play auto-provisioning feature. Users can scan the QR code to complete the registration on the Ezyphone softphone

Proxy Services

No fixed public IP, third-party DDNS services, and VPN router are required. Remote extension and remote branch office phone system integration have never been easier!

3rd Party Compatible

In addition to the built-in phone system functions, DUC-200 is also compatible with third-party SIP systems, including standard SIP endpoints, CRM systems, and collaboration tools to expand the existing IP voice communication function

Remote Management System

The control center can manage each authorized PBX in a unified manner through the remote management system, realizing remote switching off equipment, viewing real-time data, and collaborative user troubleshooting

Billing

With a built-in billing system, no third-party billing software is required. Pre-paid/postpaid billing, billing credit, flexible billing rates, and billing statistics features are all supported

Expansion Box Provisioning

The EX16S Expansion Box can help users to deploy analog phones and fax machines on a large scale in a brief time. Both local and remote deployments are equally simple and rapid collaboration tools to expand the existing IP voice communication function

Operator Panel

The Operator Panel is a comprehensive software specially designed for the CooVox series of IPPBX. By using the Operator Panel, users can achieve features such as live paging, emergency paging, high-quality background music, scheduled paging, scheduled music etc

Ezyphone Softphone

Ezyphone softphone brings users a new office phone system experience while using the CooVox IPPBX v4. Ezyphone is like a desk phone that can take your office anywhere. Users can answer calls, dial calls, and even dial international calls through the office's IPPBX. never been easier!

Software Specifications

System Capacity	<ul style="list-style-type: none">• 800 Extensions• 80 Simultaneous Calls• 60 Conference Attendees(Recommended)• 80 Conference Attendees(Maximum)• 15000 hrs Recording (Internal Storage)	<ul style="list-style-type: none">• 12 EX16S Deployment (Recommended)• Unlimited SIP/IMS Trunks (Max)• Unlimited IVR Levels• Unlimited Number of Queues• Unlimited Phonebook Contacts• Maximum 200 Paging Members	<ul style="list-style-type: none">• 500000 CDR History• 1TB USB Expansion Storage• Unlimited Number of Incoming Routes• Unlimited Number of Outbound Routes
Protocols & Codecs	<ul style="list-style-type: none">• SIP(RFC3261), IAX2• DTMF(RFC4733, SIPINFO,In-Band)• Transport Protocols:UDP,TCP,TLS,SRTP• Network Protocols:IPv4, IPv6, VLAN, DHCP, PPPoE, DDNS, NTP, SNTP, TFTP, SSH, HTTPS, LDAP• Video Codecs:VP8,H.264,H.263+,H.263,H.261• Audio Codecs:Opus, G.722, G.711(a-law,u-law), G.729, G.726, GSM, SPEEX,AMR,AMR-WB		
Telephony Features	<ul style="list-style-type: none">• Call Queue• Ring Group• Call Forward• Call Transfer• Call Pickup• Call Parking• Call Waiting• Speed Dial• IVR (Multi-layer	<ul style="list-style-type: none">• Caller ID• Call Spy• Video Call• 3-way Calling• Conference Call• Follow Me• Call Back• DISA• Sma DID	<ul style="list-style-type: none">• Blacklist• Voicemail• Wakeup Call• PIN Code• Do Not Disturb• Switch Call• Time Conditions• Paging & Intercom <ul style="list-style-type: none">• One Number Stations• Music On Ringback• Distinctive Ringtone• Auto Call Recording• One Touch Recording• Web Extensions• (WebRTC)
Feature Highlights	<ul style="list-style-type: none">• Remote Management• Softphone APP Auto Provisioning (QR Code Scan)• IP Phone Auto Provisioning (PNP & Quick Register Code)• LDAP Phonebook Auto Con gure (H81, H83)• EX16S Auto Provisioning• SIP Proxy (NAT Traversal)• Open API Interface for Seconda Development to Connect with 3rd Systems• Multilingual Interface: Simplified Chinese, Traditional Chinese, English, Spanish, Czech, Korean• Multilingual System Voice: Chinese, English, Spanish, French and other 24 languages		
Multi-level User Administration	<ul style="list-style-type: none">• Admin user: All Privileges• Operator user: Extensions, faxes, CDR, recordings, etc.• Extension user: WebRTC, recordings, voicemails, call logs, etc.• Billing user• Operator panel user		
Security	<ul style="list-style-type: none">• Firewall based on iptables• Geo-IP (Security policy based on IP address geographical locations)• Intrusion auto detection and prevention• IP Black/White List• Extension Permit IP• Data Backup and Recovery		
Network Features	<ul style="list-style-type: none">• Network (WAN): Static IP, DHCP, PPPoE• VPN:PPTP, OpenVPN,• Static Routing• DHCP Server• VLAN (WAN&LAN Interface)• Virtual IP• SIP Proxy (NAT Traversal)		

Application Scenarios



Restaurant



Venue



Retail Store



Mine



Financial
Institution



Factory



Warehouse



National Park

Hardware Specifications

	Specifications
Analog interface	2 Slots (Adapter module : FXO/FXS/GSM/WCDMA)
CPU	ARM 4 Core
RAM	1GB DDR3
Storage (SD Card)	8G SD Card (Industrial grade)+ 1TB Surveillance HDD
USB (Extended Storage Supported)	1 Po (File system format : FAT16, FAT32, EXTFAT, NTFS, EXT3, EXT4)
Ethernet Interface	WAN, LAN (10/100Mbps)
Console Port	1 Port (Rate 115200)
Reset Key	Support
Power	AC 100~240V, 50/60Hz, MAX1.5A